



GENESIS



GENESIS

A MASTERPIECE FROM THE VAN DYCK COLLECTION



CUT-PILE LOOSELAY TILES

Pile Fibre	100% Antron® Excel BCF Nylon 6.6
Backing	Enduroback KR4®
Fibre Weight	750 gsm
Total Weight	4250 gsm
Total Thickness	7 mm
Protective Finish	Stain Shield Protected
Location Grade	Heavy Commercial
Fire Rating	2
Width	50 x 50 cm

NB: Tiles to be tessellated. All sizes, 50 x 50 cm, 60 x 60 cm and 100 x 100 cm tiles as well as 366 cm broadloom with unitary backing are made to order, subject to a minimum order of 650 m².

Maintenance

Enhance the performance and appearance of your carpet by following these steps:

- Use quality Dirt Off walk off mats.
- Vacuum thoroughly and frequently.
- Remove spills and marks immediately.
- General clean by a SETA Qualified Cleaner.

>> Helpful Hint

Whilst the light colours in the range are extremely attractive, they are high maintenance. They show soil quicker than darker colours and need frequent cleaning. We accept no liability on soiling, as this is maintenance related and not a manufacturing defect.

Bill of Quantities

Looselay Tiles: GENESIS EXCEL made from 100% Antron® Excel BCF nylon 6.6, tufted cut-pile looselay carpet tiles by Van Dyck Carpets in (colour name) laid in accordance with the code of practice for the installation of textile floorcoverings (SANS 10186).



5 year guarantee

This carpet is guaranteed by Van Dyck Carpets for a period of five years against any latent defect in the manufacturing process. Claims will be treated in accordance with the South African Carpet Manufacturers Standard Claims Policy. However, carpets must have been maintained and cleaned according to Van Dyck Carpets' written instructions.



ISO Certification

Van Dyck Carpets quality management system is certified to SABS 9001:2000. This is your assurance of our commitment to maintain the highest international quality standards.



Stain Shield Protected

The Stain Shield Protection mark is your assurance that the carpet you have purchased is protected from stains and soiling. An advanced fluoro carbon protection shield is sprayed onto the carpet during the production process. Because this shield repels oily and watery stains and soil, it gives you more time to remove the offending substance before it penetrates the pile.



Torture Tunnel Tested

Every carpet manufactured by Van Dyck Carpets undergoes this unique test during which it is subjected to 75 000 footfalls.



10 year warranty

Van Dyck Carpets (Pty) Ltd offers a 10 year limited warranty against excessive fibre wear on this carpet.



Anti-allergenic

Carpeting helps trap dust and irritants, which can cause allergies. These can then be removed by regular vacuuming.